

---

## WFP Pre-Tec S-Tape

### Waterproofing sanded tape Highly flexible, perfect bonding to freshly poured concrete

<b>Product description</b>	WFP Pre-Tec S-Tape is a unique, special laminated, highly flexible tape. The tape is cold applied and pre-applied, as it is installed without heat or open-flames. It consists of an aggressive pressure sensitive adhesive and trafficable weather resistant granular coating on a self adhesive rubber with removable silicon foil on one side. The application must be done before the reinforcement steel is fixed and the concrete is poured.
<b>Area of application</b>	WFP Pre-Tec S-Tape is used secure connection and overlapping areas of WFP Pre-Tec Membrane Plus and FPO. WFP Pre-Tec S-Tape is also used as a sleeve for repair damages of WFP Pre-Tec Membrane Plus.
<b>Properties</b>	<ul style="list-style-type: none"><li>- Highly flexible</li><li>- Granular coating</li><li>- Pressure sensitive adhesive</li><li>- Continuous thickness</li><li>- Simple installation</li><li>- Watertight</li><li>- Chemical resistant</li><li>- Perfect bonding to concrete</li><li>- Weather resistant</li><li>- UV-resistant for &gt;60 days</li><li>- Trafficable</li><li>- Crack-bridging</li><li>- Not harmful for groundwater</li></ul>

**Specification**

Base:	Rubber adhesive
Self adhesive coating:	polymer
Color:	sanded blue
Processing temperature:	> + 5°C to + 45°C
Thickness:	approx. 1.0 mm
Length according to DIN EN 1848-2:	20 m
Width according to DIN EN 1848-2:	100 mm

**Delivery form**

Rolls á 10 cm x 20 m

**Storage**

24 months (cool and dry in the original package)

**Application**

See technical data sheet of WFP Pre-Tec Membrane Plus.

**Disclaimer**

The information complies with the current state of development. There is no claim for completeness. A professional and therefore successful processing of the products is not within our responsibility. We accept a warranty only for the quality of the products, but not for processing. It is the responsibility of the user to evaluate the suitability of our products for its purpose. Preliminary tests are recommended.