



## WFP Pre-Tec Tape

### Waterproofing self adhesive HDPE-tape Highly flexible

#### Product description

WFP Pre-Tec Tape is a HDPE tape with self adhesive coating on one side. The tape is cold applied and pre-applied, as it is installed without heat or open-flams. It consists of an aggressive pressure sensitive adhesive on a HDPE membrane with silicon foil on one side. The application must be done before the reinforcement steel is fixed and the concrete is poured.

#### Area of application

WFP Pre-Tec Tape is used at end laps overlapping areas of WFP Pre-Tec Membrane Plus and FPO.

#### Properties

- Highly flexible
- Pressure sensitive adhesive
- Continuous thickness
- Simple installation
- Watertight
- Highly chemical resistant
- Perfect bonding to concrete
- Weather resistant
- Methane barrier
- UV-resistant for >60 days
- Trafficable
- Crack-bridging
- Not harmful for groundwater

**Specification**

Base:	flexible membrane
Self adhesive coating:	polymer resin with granulate
Color:	white
Thickness:	approx. 1.0 mm
Length according to DIN EN 1848-2:	20 m
Width according to DIN EN 1848-2:	150 mm

**Delivery form**

Rolls á 15 cm x 20 m (W140115)  
Rolls á 20 cm x 20 m (W140120)

**Storage**

24 months (cool and dry in the original package)

**Application**

See technical data sheet of WFP Pre-Tec Membrane Plus.

**Disclaimer**

The information complies with the current state of development. There is no claim for completeness. A professional and therefore successful processing of the products is not within our responsibility. We accept a warranty only for the quality of the products, but not for processing. It is the responsibility of the user to evaluate the suitability of our products for its purpose. Preliminary tests are recommended.